

PRODUCT SPECIFICATIONS

DH-HAC-HFW2100B

1.3Megapixel 720P Water-Proof IR HDCVI Camera



Features

- 1/3" 1.3 Megapixel CMOS
- 25/30/50/60fps@720P
- High Speed , Long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 6mm fixed lens (2.8, 3.6mm, 8mm optional)
- Max. IR LEDs Length 30m, Smart IR
- IP66, DC12V

Technical Specifications

Model	DH-HAC-HFW2100BP	DH-HAC-HFW2100BN
--------------	-------------------------	-------------------------

PRODUCT SPECIFICATIONS

Camera	
Image Sensor	1/3" 1.3Megapixel CMOS
Effective Pixels	1280(H)×960(V)
Electronic Shutter Speed	4/25s~1/45,000s 4/30~1/54,000s
Video Frame Rate	1280x720@25fps; 1280x720@30fps; 1280x720@50fps; 1280x720@60fps
Synchronization	Internal
Min. Illumination	Color: 0. 2Lux/F1.4, B/W: 0.01Lux/F 1.4; 0Lux/F1.2(IR on)
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	30m, Smart IR
Day/Night	Auto(ICR)/Color/B/W
Noise Reduction	3D/2D
OSD Menu	Support
Lens	
Focal Length	6mm (2.8 mm, 3.6mm, 8mm optional)
Mount Type	M12
General	
Power Supply	DC12V±10%
Power Consumption	Max 6W
Working Environment	-30°C~ +60°C Humidity is less than 95%(no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions(W×D×H)	89.1mm×200.2mm×80.4mm
Weight	580g

PRODUCT SPECIFICATIONS

Dimensions (mm)

