

PRODUCT SPECIFICATIONS

DH-HAC-HFW2100S

1.3 Megapixel 720P Water-Proof IR HDCVI Camera



Features

- 1/3" 1.3MegapixelCMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 6mm fixed lens (2.8mm, 3.6mm, 8mm optional)
- Max. IRLEDslength20m, Smart IR
- IP66,DC12V

Technical Specifications

Model	DH-HAC-HFW2100BP	DH-HAC-HFW2100BN
Camera		
Image Sensor	1/3" 1.3Megapixel CMOS	
Effective Pixels	1280(H)x960(V)	
Electronic Shutter Speed	4/25s ~ 1/45,000s	4/30~1/54,000s

PRODUCT SPECIFICATIONS

Synchronization	Internal
Min. Illumination	0.01 Lux@F1.2(0Lux IR LED on)
Video Output	1-Channel BNC HDCVI high definition video output/CVBS standard definition video output (Can Switch)
Camera Features	
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
Noise Reduction	2D
OSD Menu	Support
Lens	
Focal Length	6mm (2.8mm, 3.6mm, 8mm optional)
Mount Type	M12
General	
Power Supply	DC12V±10%
Power Consumption	Max 4.2W
Working Environment	-30°C~+60°C / Less than 95%RH(no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions	Φ65mm×154.7mm
Weight	380g
Others	Default bracket included

PRODUCT SPECIFICATIONS

Dimensions (mm)

