

PRODUCT SPECIFICATIONS

DH-HAC-HDW2100S

1.3 Megapixel 720P Water-Proof IR HDCVI Camera



Features

- 1/3" 1.3MegapixelCMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 6mm fixed lens (2.8mm, 3.6mm, 8mm optional)
- Max. IRLEDslength20m, Smart IR
- IP66,DC12V

Technical Specifications

Model	DH-HAC-HDW2100SP	DH-HAC-HDW2100SN
Camera		

PRODUCT SPECIFICATIONS

Image Sensor	1/3" 1.3Megapixel CMOS	
Effective Pixels	1280(H)x960(V)	
Electronic Shutter Speed	4/25s ~ 1/45,000s	4/30~1/54,000s
Synchronization	Internal	
Min. Illumination	0.01 Lux@F1.2(0Lux IR LED on)	
Video Output	1-Channel BNC HDCVI high definition video output/CVBS standard definition video output (Can Switch)	
Camera Features		
Max. IR LEDs Length	20m, Smart IR	
Day/Night	Auto(ICR)/Color/B/W	
Noise Reduction	3D/2D	
OSD Menu	Support	
Lens		
Focal Length	3.6mm (2.8mm, 6mm 8mm optional)	
Mount Type	M12	
General		
Power Supply	DC12V±10%	
Power Consumption	Max 3.5W	
Working Environment	-30°C~+60°C / Less than 95%RH(no condensation)	
Transmission Distance	Over 500m via 75-3 coaxial cable	
Ingress Protection	IP66	
Dimensions	Φ113.6mm×85.4mm	
Weight	300g	

PRODUCT SPECIFICATIONS

Dimensions (mm)

