

HAC-HDBW1100R-VF

1Megapixel 720P Vandal-proof IR HDCVI Dome Camera



Features

- 1/2.9" 1Megapixel CMOS
- 25/30fps@720P
- High speed, long distance real-time transmission
- Day/Night(ICR), AWB, AGC, BLC, 2D-DNR
- 2.7~12mm vari-focal lens
- Max. IR LEDs length 30m, Smart IR
- IP66, IK10, DC12V

Technical Specifications

| Model | HAC-HDBW1100RP-VF | HAC-HDBW1100RN-VF |
|------------------------|--|-------------------|
| Camera | | |
| Image Sensor | 1/2.9" 1Megapixel CMOS | |
| Effective Pixels | 1280(H)×720(V) | |
| Electronic Shutter | 1/50s~1/100,000s | 1/60s~1/100,000s |
| Video Frame Rate | 25fps@720P | 30fps@720P |
| Synchronization | Internal | |
| Min. Illumination | 0.01Lux@F1.2(AGC ON), 0Lux IR on | |
| Video Output | 1-channel BNC HDCVI high definition video output | |
| Camera Features | | |
| Max. IR LEDs Length | 30m, Smart IR | |
| Day/Night | Auto(ICR) / Color / B/W | |
| Noise Reduction | 2D | |
| Lens | | |
| Focal Length | 2.7~12mm | |
| Lens Type | Manual / Fixed Iris | |
| Mount Type | Φ14 | |
| General | | |
| Power Supply | DC12V±10% | |
| Power Consumption | Max 5W | |
| Working Environment | -30°C~+60°C / Less than 95%RH (no condensation) | |
| Transmission Distance | Over 500m via 75-3 coaxial cable | |
| Ingress Protection | IP66 & IK10 | |
| Dimensions | Φ122mm×89mm | |
| Weight | 0.45kg | |

Dimensions (mm)

